


MS5/8PIU-4 (P.143-UP)

Produktübersicht:

Multischalter mit integriertem Netzteil, Quad LNB tauglich, Attenuators 0 bis 15 dB, schaltbarer aktiv/passiv terr. Eingang

Kurze Beschreibung:

5in/8out stand-alone Multischalter für Distribution von terrestrischen und SAT-Signalen von 1 SAT-Position bis zu 8 Teilnehmern.



Technische Daten:

Parameter	Bedingung	Wert
Frequency range	Sat. inputs	950-2300 MHz
	Terr. input	5-862 MHz (passive), 40-862 MHz (active)
	Outputs	5-2300 MHz (passive), 40-2300 MHz (active)
Control		13/18 V + 0/22 kHz
Insertion loss	Sat.	4 dB avg
	Terr. active	3 dB avg
	Terr. passive	20 dB avg
Sat. inputs isolation		20 dB min
Maximum input level*	Sat.	90 dB μ V avg**
	Terr.	100 dB μ V avg (passive), 93 dB μ V avg (active)
Maximum output level*	Sat.	86 dB μ V avg
	Terr.	80 dB μ V avg (passive) 90 dB μ V avg (active)
Power consumption	From each receiver	40 mA (18 V)
	From internal power supply	4 W (passive) + LNB 6 W (active) + LNB
Terr. preamplifier supply		100 mA max (12 V DC)
Dimensions (w,d,h)		27.0 x 15.2 x 8.7 cm (power cord length 130 cm)
Temperature range		-30 ~ +70 °C
Weight		1.200 kg

*Terr.: EN 50083-3/60dB IMA3 [dB μ V]; SAT: EN 50083-3/35dB IMA3 [dB μ V]